

800 SERIES



PRESSURE WASHERS / SINCE 1970

FEATURES

3.5 to 5 GPM @ 2000 to 3000 PSI
Stainless Steel Coil Skin
5 - 10 HP



HOT WATER

ELECTRIC

BELT DRIVE

Upright, oil fired burner delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil

50-ft. length of high-pressure hose for ease in cleaning around a large area

Protective cabinet contains water resistant electrical box

Float tank helps maintain constant water pressure and flow while helping to prevent sediment from entering the machine's components

Forklift slots for easy lifting

Rust-proof, removable, non-contaminating polyethylene fuel tank includes fuel gauge in cap

Wide wheel base for stability, but 28" width easily fits through doors

Easily removable **cover** provides protection and easy access to components

35-ft. power cord with safety **Ground Fault Circuit Interrupter (GFCI breaker)** *single phase only

Beefy casters for easy movement

12" solid rubber tires for easy maneuvering; eliminates risk of flats

On board **wand and cord storage**

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning

Stainless-steel coil skin provides extra durability to withstand the elements

Pressure relief valve protects the machine and user from thermal expansion

Simple, easy-to-use control panel includes adjustable thermostat

Hose-reel slot accepts swivel or stationary reels for ease in hose management and storage

Reliable, energy efficient **oil burner** is built to provide years of trouble free service

Hotsy-designed **Triplex Pumps** carry a 7-year limited warranty and **Heater Coil** carries a 5-year warranty

U.S. Design Patent No. 726,382 S



Optional Detergent Bucket Bracket



OPTIONS FOR 800 SERIES

Auto Start/Stop Kit

Thermal Shutdown Kit

Time Delay Shutdown

8" Oil-Fired Vent Regulator

360° Pivot Reel, 100'

360° Pivot Reel, 200'

Pneumatic Wheel

Detergent Bucket Bracket