

ET HANDHELD SERIES



PRESSURE WASHERS / SINCE 1970

FEATURES

1.8 GPM @ 1400 PSI or 3 GPM @ 1000 PSI; 2 HP

COLD WATER

ELECTRIC

DIRECT DRIVE



Model ET-301109D

25° high pressure **Quick Connect Nozzle** conveniently mounts to unit

Heavy-duty Hotsy Trigger Gun with chrome plated wand with side handle

50 ft. steel wire-braided **High Pressure hose** rated for up to 4000 PSI. With 24-inch Hose Guard and swivel fitting for tangle-free handling

Model ET-201409DX2

The **ET-201409DX2** features Auto Start-Stop, which allows the operator to start and stop the washer by pulling or releasing the trigger gun; this also provides additional protection for the high-pressure pump

25° high pressure **Quick Connect Nozzle** conveniently mounts to unit

Spring-loaded Trigger Gun with two-piece, twist-lock, easy grip Spray Wand

25 ft. steel wire-braided **High Pressure hose** rated for up to 3000 PSI. With 24-inch Hose Guard and swivel fitting for tangle-free handling

Remote wall switch with 10-foot electrical cord for convenience in turning the washer on in wash bay installations



ET SERIES

Thermal pump protector prevents excessive heat or pressure buildup for safety

The reliable **Hotsy Triplex pump** carries a 7-year limited warranty....best in the industry

Pressure-trapping unloader safety feature diverts water flow when trigger gun is not in use

Rubber pads absorb vibration for long-life and to keep the unit from moving or "walking" while in operation

Reliable industrial Motor with **1725 RPM**, reset button, capacitor start and full-service factor for longer life

36 ft. Electric Cord with NEC approved ground fault circuit interrupter for operator protection

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	PUMP MODEL	HOSE (FT)	DIMENSIONS	SHIP WT (LBS)
ET-301109D	1.106-107.0	3.0	1000	2.0	115/1	HF2830S	50	20"x19"x17"	121
ET-201409DX2	1.107-089.0	1.8	1400	2.0	115/1	HFP2030S	25	20"x19"x17"	123



HOTSY.COM

THE BRAND THE PROS USE

Distributed by:

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_10% and in some cases are tighter within +_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 2021 Kärcher North America
P/N HOT_CWC Effective 06/21